

## TOP LOAD HOT AIR DRYERS



Top Load Dryers are designed for use in industrial applications where production requirements and efficiency are the primary criteria. Although they offer larger work chambers than the MT style dryers, they are not constructed with an outer bench enclosure, and are therefore somewhat less expensive than their MT counterpart. These units offer insulated, double-wall stainless steel construction, high velocity blower, and digital readout thermostat. They are available with rod-style rack hangers or a removable work rest.

Model #	Internal Dimensions	Overall Dimensions	Power Requirements	
			Electrically Heated	Steam Heated
<b>TL3025</b>	27" x 25" x 30"	64" x 42" x 41"	230V/3PH-25A	120V/1PH-15A
<b>TL4825</b>	45" x 25" x 30"	77" x 42" x 41"	230V/3PH-25A	120V/1PH-15A
<b>TL6025</b>	57" x 25" x 30"	89" x 42" x 41"	230V/3PH-25A	120V/1PH-15A
Custom Sizes and voltages available.				
Design specifications for standard models are subject to change without notice.				



### **Greco Brothers Incorporated**

1 Greco Lane  
Providence, Rhode Island 02909-2616  
401/421-9306 fax: 401/274-8910  
[www.grecobrothers.com](http://www.grecobrothers.com)